



Total Glass Solution
SINCE 1990

SPECIFICATIONS

- ▶ **Available thickness** - 4mm - 19mm
- ▶ **Sheet Size** – Minimum 300x300 and maximum 3660x2440
- ▶ **Solar factor** – 39 – 81
- ▶ **Light reflection** – 4% - 35% (depend on glass)
- ▶ **Available color** - Green, Clear, Gray, Brown and etc.
- ▶ **Available Reflecting Range** - Supersilver Clear, Supersilver Green, Super silver Blue, Stopsol Classic Bronze, Stopsol Classic Green, Stopsol Classic Blue

APPLICATION

- ▶ **House**
- ▶ **Office**
- ▶ **Building**
- ▶ **Shopping Malls**
- ▶ **Industry**

FEATURES

- ▶ **Available size** – 3660mm x 2440mm (3.66 meter x 2.44 meter)
- ▶ **Available in different thickness** - 4mm to 19mm
- ▶ Superior glass retention properties
- ▶ Surface compression
- ▶ Known for safety, strength and style

APPLICATION

- ▶ **Shape cutting**
- ▶ **Stair finish edge**
- ▶ **Etching and screen printing**
- ▶ **Frosting & Sand blasting**
- ▶ **Hole & Counter cut-out**
- ▶ **Polished & Beveled edge**

HEAT STRENGTHENED GLASS



TOUGHENED GLASS



SPECIFICATIONS

- ▶ Light transmittance
- ▶ Reflective Glass
- ▶ Higher strength & security
- ▶ Min size: 300x300mm
- ▶ Max size: 3660x2440 & Extra Large 4260x2440
- ▶ No edge corner which can injure the user

APPLICATION

- ▶ **Windows**
- ▶ **Building Glass**
- ▶ **Mall Glass**
- ▶ **Glass doors**
- ▶ **Cook-ware and in house for windows and clear glass feature**
- ▶ **Industrial uses - aircraft, space, automotive, architectural and nuclear**



SPECIFICATIONS

- ▶ Provides pleasant room temperature
- ▶ Lends high standard finish
- ▶ Light weight & Smooth edges
- ▶ Lower air conditioning and heating costs
- ▶ Lower UV transmission

APPLICATION

- ▶ Airports and buildings
- ▶ Train windows
- ▶ Airport control towers
- ▶ Office buildings, hospitals, hotels, houses

SPECIFICATIONS

- ▶ **Max Size:** 3660 x 2440 mm
- ▶ **Min Size:** 300 x 300 mm
- ▶ **Thickness:** 4 mm to 19 mm
- ▶ High anti-aging and optics performance
- ▶ Explosion and bullet resistance
- ▶ Storage at normal temperature

APPLICATION

- ▶ Show room & shopping malls
- ▶ Banks & underwater constructions
- ▶ Leisure complexes
- ▶ Skylight glazing
- ▶ Glass railing panels & Glass staircases



LAMINATED GLASS

PVB LAMINATED GLASS



SPECIFICATIONS

- ▶ Safety & security glass
- ▶ UV control
- ▶ Low visual distortion
- ▶ Environment protection
- ▶ Noise reducing glass
- ▶ Reliable and low maintenance product

APPLICATION

- ▶ Glass railing panels & Glass staircases
- ▶ Show room & shopping malls
- ▶ Banks
- ▶ Construction
- ▶ Leisure complexes
- ▶ Skylight glazing



SPECIFICATIONS

- ▶ Clear and transparent visualization
- ▶ Customer specific production facility
- ▶ Stronger than conventional glass
- ▶ Fine finished and attractive patterns
- ▶ Weather protection

APPLICATION

- ▶ Window
- ▶ Door
- ▶ Glass roof building
- ▶ Glass curtain wall
- ▶ Windshields of automobiles
- ▶ Ships and places needing bullet or blast resistance

SPECIAL FEATURES

- ▶ Extra Transparent bullet proof glass
- ▶ Water repellent bullet proof glass
- ▶ Increase light transmission
- ▶ Innovative and attractive patterns
- ▶ Safe and secure glass

APPLICATION

- ▶ Military Forces Vehicles
- ▶ Military tanks
- ▶ Civilian Vehicles
- ▶ Capable to bear high blast, bullet
- ▶ Jewelry shops
- ▶ Aircrafts



BULLET PROOF GLASS

CERAMIC FRITTED & BACK PAINTED GLASS



SPECIAL FEATURES

- ▶ Available in thickness from 4mm to 19 mm
- ▶ Available in various colors and designs
- ▶ Maximum Size 3660 x 2400 mm
- ▶ Minimum Size 300 x 300 mm
- ▶ Customized color and design facility

APPLICATION

- ▶ Office and lobby decor
- ▶ Bathroom vanity tops
- ▶ Refrigerator and cabinet door panels
- ▶ Elevators & Kitchen backsplashes
- ▶ Colored Glass Doors
- ▶ Cabinet glass inserts



SPECIAL FEATURES

- ▶ **Max. Glass size:** 3660 × 2440mm
- ▶ **Min. glass size:** 300 × 300mm
- ▶ **Glass Thickness:** 5mm, 6mm, 9mm, 12mm, 15mm
- ▶ Insulating glass thickness: 40mm
- ▶ Avoids the risk of condensation
- ▶ Heat insulation & Sound insulation

APPLICATION

- ▶ Glass curtain walls
- ▶ Glass doors
- ▶ Glass windows

SPECIAL FEATURES

- ▶ Thickness from 4 mm to 19 mm
- ▶ Maximum Size 3660 x 2440 mm
- ▶ Minimum Size 300 x 300 mm
- ▶ Stronger and user friendly products
- ▶ Standard as well customized solutions

APPLICATION

- ▶ Executive Room Partitions
- ▶ Shower Room Partitions
- ▶ Hospitals
- ▶ Hotels



DGU GLASS

INSULATED GLASS BLINDS



SPECIAL FEATURES

- ▶ Individual switch & remote control system (Electronic control panel)
- ▶ Stylish and safe solution
- ▶ Sealed within the glazed unit
- ▶ Energy saving product
- ▶ Provide excellent light-filtering control

APPLICATION

- ▶ Conference room & board room
- ▶ Separators as cabins and cubicles
- ▶ Bathroom air-vents
- ▶ Kitchen and dining room partitions